

The TRIUMPH Corporation

Parts - Tools - Accessories Bulletin

April 20, 1967

Bulletin 67-8P

MOUNTING INSTRUCTIONS FOR CD469 COMBINATION LUGGAGE RACK/SEAT RAIL 1963 to 1966 "B" and "C" Range Machines

Hardware

- | | |
|---|-----------------------------------|
| 2 | 1/4-28 x 1 1/4 Hex Head Cap Screw |
| 2 | 1/4-28 Hex Nut |
| 2 | 1/4 Lockwasher |
| 2 | 1/4 x 3/4 OD x 5/8 length Spacer |
| 1 | 5/16-24 x 3/4 Hex Head Cap Screw |
| 1 | 5/16-24 Hex Nut |
| 1 | 5/16 Star Washer |
| 1 | 5/16 x 3/4 x 1/4 length Spacer |

Late 1966 models must use F7850 lifting handle. The bend on the left side of late 1966 lifting handles interferes with the left side rail of the Luggage Rack.

Mount the luggage rack to the frame by attaching the side rail to the holes in the frame just in front of the top shock mounts with the two 1/4-28 x 1 1/4 hex head cap screws, two 1/4-28 hex nuts, two 1/4 lockwashers and two 1/4 x 3/4 OD x 5/8 length spacers. These spacers are placed between the side rails of the luggage rack and the motorcycle frame. Remove the rear bolt of the fender clip that attaches fender to rear frame. Attach the front cross rail of the rack to the rear bolt hole of fender clip using 5/16-24 x 3/4 cap screw, 5/16 hex nut, Star washer and 5/16 x 3/4 spacer. Spacer is placed between fender clip and front cross rail.

NOTE: When fitting saddlebags to this carrier CD466/B Bracket Set must be used for "B" Range and CD466/C Bracket Set for "C" Range machine.

MOUNTING INSTRUCTIONS FOR CD466B AND CD466C SADDLE BAG MOUNTING BRACKETS

"B" Range

Attach lower front to muffler bolt. Attach upper rear to rear hole in side plate of luggage rack.

"C" Range

Attach lower front by pillion footrest bolt. Attach upper rear to rear hole in side plate of luggage rack.